HeatMaster 25 Evo 2


Commercial combi boiler

Peak 1st hour: 577 l/h.
Continuous flow
473 l/h (at 60°C)

Tank-in-tank heat
exchange technology

ErP
class A

Exceeds all current
legislation requirements



Up to 25kW of
heating load

Internal
time clock

5

5 year
warranty*

kiwa
CERTIFIED
KUKreg4
ATS 3

A XXL

CE

acv.com/gb |

*Terms and conditions apply visit acv.com/gb for more information

HeatMaster 25 Evo 2
Technical data & dimensions

Performance

Maximum heat input NCV (GCV)	kW	25 (27.8)
Minimum heat input	kW	5
Maximum output (80/60)	kW	24.3
Maximum output (50/30)	kW	26
Efficiency at 100% load (80/60)	%	97.3
Efficiency at 100% load (50/30)	%	103.9
Efficiency at 30% load (EN 15502-1) nett	%	108.9
Seasonal Efficiency Part L (Heating)	%	97.9

ErP

Water heating efficiency class	-	A
Space heating energy efficiency class	-	A
Seasonal space heating efficiency (ErP)	%	93
Seasonal water heating efficiency (ErP)	%	93.2
Standby loss DT 30K	W	79
Standby loss DT 45K	W	124
Declared load profile	-	XXL
Sound power level indoors LWA (BSEN15036-1)	dB	60

Combustion

Gas Inlet Pressure (NG)	mbar	18-23
Gas flow rate (max output)	m3/h	2.66
Nox class (EN15502)	-	6
Nox weighted (GCV) (EN15502)	mg/kWh	24.6

Flue

Flue connection	-	80/125
Max allowed flue pressure drop	Pa	95

Hydraulic

Water pressure drop boiler at 20°C ΔT	mbar	3
Primary flow rate at 20°C ΔT	l/h	1100
Primary flow rate at 20°C ΔT	l/s	0.31

Electrical


Voltage	V	230
Fuse Rating	A	16
Electrical power consumption Max	W	101
Electrical power consumption Standby	W	3

General

Storage capacity (total)	L	196
Storage capacity (domestic hot water)	L	96
Connection - heating	-	1" F
Connection - DHW	-	1" M
Connection - gas	-	3/4" M
Max operating temperature (primary)	°C	87
Max operating temperature (DHW)	°C	75
Max service pressure heating (primary)	bar	3
Max service pressure (DHW)	bar	8.6
Weight (empty)	kg	177
Weight full	kg	373

DHW Performance - Primary Temperature - 80°C

Peak 10 min flow @ 40°C (30°C ΔT)	L/10'	361
Peak 1st hour flow @ 40°C (30°C ΔT)	L/60'	1018
Continuous flow @ 40°C (30°C ΔT)	L/h	788
Peak 10 min flow @ 45°C (35°C ΔT)	L/10'	301
Peak 1st hour flow @ 45°C (35°C ΔT)	L/60'	865
Continuous flow @ 45°C (35°C ΔT)	L/h	676
Peak 10 min flow @ 60°C (50°C ΔT)	L/10'	183
Peak 1st hour flow @ 60°C (50°C ΔT)	L/60'	577
Continuous flow @ 60°C (50°C ΔT)	L/h	473
Heat up time (Primary: 10-80°C)	mins	35



All dimensions in mm.

Minimum Clearances			
Top	**Left side**	**Right side**	**Rear**
300mm	600mm	250mm	400mm

This data assumes an incoming mains water temperature of 10°C. *In line with the recommendations specified in UK Building Regulations (2016) Part G, ACV UK Ltd advise the installation of a suitable domestic hot water thermostatic mixing valve on the hot flow immediately after the appliance.

Please contact ACV UK for details of flow rates and pressure drops at other system differentials.

Every effort has been taken to ensure the details are accurate. ACV UK Limited does not, however, guarantee the accuracy or completeness of any information nor does it accept liability for any errors or omissions in the information. ACV UK Limited reserves the right to make changes and improvements which may necessitate alteration to product specification without prior notice.