

EVO S

150kW



Condensing boiler with stainless steel heat exchanger technology.

Features


- > Robust stainless steel heat exchanger
- > NOx class 6 for all models
- > 5:1 turndown
- > Large product range up to 150kW
- > 6 bar max operating pressure (80kW and above)
- > Cascade ability of up to 900kW (exceptions apply)
- > Compact design
- > Full suite of cascade accessories available
- > Energy efficiency class A
- > Full range of hydraulic separation options available
- > Pump modulation controls built into boiler software
- > 20% hydrogen blend ready

5

5 year warranty*

Dimensions and Clearances

Boiler	Dimension A	Dimension B	Dimension C	Dimension D
150kW	487mm	668mm	895mm	408mm



The following minimum clearances must be maintained for operation and servicing:

- TOP**
Between 145 and 450mm depending on flue system type
- FRONT**
800mm
- SIDES**
250mm clearance between end boiler and closest wall

EVO S		
	Unit	150kW
Part Number		100008264700
Performance		
Nominal heat input Qn	kW	145
Minimum heat input Qmin	kW	29
Modulation		5:1
Nominal output Pn (80/60)	kW	141.1
Nominal output (50/30)	kW	154.5
Max total cascade output (80/60)	kW	847
Thermal efficiency - 100% GCV	%	97.4
Thermal efficiency - 30% NCV	%	108.6
Part L 2022 seasonal efficiency	%	95.8
Seasonal space heating efficiency (ErP)	%	93
Space heating energy efficiency class		n/a
Standing loss	W	69
Combustion		
Min/Max gas pressure (NG)	mbar	17/25
Gas flow rate at Pn (15°C) (NG)	m ³ /h	15.3
NOx Emissions according to EN 15502-1 (Gross)	mg/kWh	39
NOx class		6
Hydraulic		
Flow rate at nominal heat input Qn	m ³ /h	6.23
Flow rate at minimum heat input Qmin	m ³ /h	3.44
Maximum operating pressure	bar	6
Minimum operating pressure	bar	1
Maximum operating temperature	°C	85
Water content	L	11
Sound power at Pmax Lw	dB(A)	59.2
System Hydraulic Info (NG & LPG)		
Hydraulic resistance (ΔT 11 °C)	mbar	2278
Flow rate (ΔT 11 °C)	l/min	188.3
Hydraulic resistance (ΔT 15 °C)	mbar	1223
Flow rate (ΔT 15 °C)	l/min	138.1
Hydraulic resistance (ΔT 20 °C)	mbar	701
Flow rate (ΔT 20 °C)	l/min	103.6
Hydraulic resistance (ΔT 25 °C)	mbar	441
Flow rate (ΔT 25 °C)	l/min	82.9
Max system temp differential	°C	30*
Hydraulic resistance (ΔT 30 °C)	mbar	313
Flow rate (ΔT 30 °C)	l/min	69.1

*Boilers must be at maximum load to achieve this temperature differential

EVO S		
	Unit	150kW
Part Number		100008264700
Flue		
C = Concentric Flue, B = Open Flue		
Approved flue systems		B23, B23P, C13, C33
Flue size		100/150
Concentric flue system max length (NG)	m	6
Max allowable nozzle pressure open flue (80/60) NG	Pa	190
Max allowable nozzle pressure open flue (50/30) NG	Pa	170
Flue gas mass flow rate (80/60) NG	g/s	67.5
Flue gas mass flow rate (50/30) NG	g/s	60.8
Electric		
Electrical supply		230V - 50Hz
Power consumption at Qn	kW	0.26
Power consumption in standby mode	kW	0.003
Physical		
Dry weight	kg	100
Gas supply connection		G 1"
Flow/Return connections		G 1 1/4"
Clearances - front of boiler (service clearance)	mm	800
Clearances - boiler to wall	mm	250
Clearances - above boiler casing (B23/B23P flue)	mm	289
Clearances - above boiler casing (C13 flue)	mm	325
Clearances - above boiler casing (C33 flue)	mm	145
Available Accessories		
Inline cascade kits		✓
High efficiency boiler pump		✓
Bespoke low loss headers		✓
Pre-sized PHEXs		✓
Additional circuit control kits		✓
Modbus communication gateway		✓
Temperature sensor kits		✓
Remote run/fault signalling kit		✓

ACV UK Ltd

St. David's Drive, St. David's Business Park, Dalgety Bay, Fife, KY11 9PF
 uk.sales@acvuk.com | acv.com/gb



Every effort has been taken to ensure the details are accurate. ACV UK Limited does not, however, guarantee the accuracy or completeness of any information nor does it accept liability for any errors or omissions in the information. ACV UK Limited reserves the right to make changes and improvements which may necessitate alteration to product specification without prior notice.